

Product Data Sheet Mobil Gargoyle Arctic Oil 155 and 300

Refrigeration Oils

Product Description

Mobil Gargoyle Arctic Oil 155 and 300 are high performance naphthenic mineral oils primarily intended for use in refrigeration compressors. They have low pour points and excellent fluidity at very low temperatures by virtue of being almost wax-free. Consequently, use of these Gargoyle Arctic Oils ensures that evaporator tubes are kept clean to improve heat transfer and to reduce downtime for maintenance. They have good chemical stability and are suitable both for cylinder and bearing lubrication.

Gargoyle Arctic Oil 155 and 300 are compatible with all refrigerants except sulphur dioxide. They are not recommended for use with HFC refrigerants. The moisture content is very low when the oils are packaged. Every precaution should be taken to keep the oils dry to avoid the formation of ice in expansion valves, and to limit the risks of oil degradation, copper plating, etc.

Features & Benefits

The Mobil Gargoyle Arctic Oil brand of refrigeration oils enjoy a world-wide reputation for good performance based on their use in a wide variety of refrigeration applications over the past several decades. Mobil Gargoyle Arctic Oil 155 and 300 were the pioneers of this brand and are specially manufactured to provide the specific properties required for refrigeration equipment. Not least among these are low pour point. Mobil Gargoyle Arctic Oil 155 and 300 offer the following features and potential benefits:

Features	Advantages and Potential Benefits
Low wax content	Excellent low temperature flow and evaporator heat transfer for optimum system efficiency
Good chemical stability	Long service life resulting in less downtime and lower maintenance costs
Multi-purpose lubricants	Suitability for the lubrication of both cylinders and bearings reduces oil inventories

Applications

Mobil Gargoyle Arctic Oil 155 and 300 products are recommended for cylinder and bearing lubrication in all conventional refrigeration compressors and for all other machinery operating at sub-zero temperatures. Typical applications include:

- Large industrial reciprocating and rotary refrigeration compressors.
- Industrial applications such as food freezing and cold storage plants
- Marine refrigeration applications
- Used primarily with ammonia refrigerant, but also used with selected halocarbons

Typical Properties

Mobil Gargoyle Arctic Oil	Test Method	155	300
ISO VG		32	68
Viscosity, cSt at 40°C	ASTM D 445	32.0	68.0
Flash Point, °C	ASTM D 92	190	200
Pour Point, °C	ASTM D 93	-42	-42
Specific Gravity at 15°C/15°C	ASTM D 1298	0.91	0.91
Total Acid Number, mg KOH/g	ASTM D 974	0.01	0.01
Flocculation Point, R 12, °C	DIN 51351	-36	-31

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDSs are available upon request through Esso Petroleum Company Ltd., by telephoning 01372 222000. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment.

Esso Petroleum Company Limited
ExxonMobil House, Ermyn Way
Leatherhead, Surrey, KT22 8UX
Telephone: 01372 22 2000



Due to continual product research and development, the information contained herein is subject to change without notification.

Typical Properties may vary slightly.

All products may not be available locally.

The Mobil logotype, the Pegasus design are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

© 2001 Exxon Mobil Corporation. All rights reserved.